## **Technical**

## **Data Sheet**



Willamette Valley Company www.wilvaco.com

800.333.9826

Partnering through service, innovation, and integrity

## **WESTERN DIVISION**

660 McKinley Street Eugene OR 97402

Tel. 800.333.9826

#### **EASTERN DIVISION**

6662 Marbut Road Lithonia GA 30058

Tel. 888.878.9826

## MIDWEST DIVISION

1549 Hwy 2 Two Harbors MN 55616

Tel. 218 834 3922

### SOUTHERN DIVISION

100 Dixie Mae Drive Pineville LA 71361

Tel. 800 444 9826

# **CBS-156 GP BLUE XLS**

## **Edge Sealer for Composite Boards**

## DESCRIPTION

Willamette Valley Company has formulated CBS-156 GP Blue XLS, as a cost effective 32.5% solids composite board sealer specifically designed to meet the needs of the composite board industry. CBS-156 GP Blue XLS maintains the dimensional stability of the panels exposed to moisture by forming an elastomeric film barrier that fills voids, and is both effective and long lasting.

## WHERE TO USE

- Composite Board Edge Sealer
- Industrial Mill Environments

## **FEATURES AND BENEFITS**

- Excellent Moisture Protection
- Increases Wood Shelf Life
- Fills Voids to Seal Effectively
- Long Lasting Moisture Barrier

### PACKAGING

5-gallon pails

Drums

Totes

Tank Trucks

#### SHELF LIFE

3 months when properly stored. Will require agitation.

#### **STORAGE**

Store this product in a clean, dry, shaded or covered environment above 45°F (7.2°C). DO NOT FREEZE.

## **TECHNICAL INFORMATION**

## TYPICAL PROPERTIES

pH pH		9.2
Weight / Gallon — lbs./gal. (kg / L)		8.24(.99)
Coverage, ft <sup>2</sup> . / U.S. gal. (m <sup>2</sup> / L)	4-5 wet mils	350 (8.6)
	8-10 wet mils	175 (4,.3)
Solids by weight		32.5%
Viscosity at 78°F (25.5°C) (centipoise)		1050
Color		GP Blue

## **APPLICATION**

Apply one coat of CBS-156 GP Blue XLS Sealer by airless spray at a film thickness of 8-10 wet mils. You can increase the film thickness for porous wood or to obtain a higher performance. Check with your Willamette Valley Company representative for directions and recommendations for use with other types of application methods. Stenciling or any recoating process should be done before the sealer has dried completely and formed an impervious film.

#### **CLEAN-UP**

The Composite Board Sealer CBS-156 GP Blue XLS can be washed off with water prior to the film drying. If the sealer has dried, scrubbing with hot water and detergent is advised.

#### NOTES

This product is supplied to the customer in a ready-to-use form. Any addition of water will result in degradation of the product performance.

## **HEALTH AND SAFETY**

Before handling, you should become familiar with the Material Safety Data Sheet (MSDS) regarding the risks and safe use of this product. To obtain an MSDS please call 800-333-9826 or send an email to: msds@wilvaco.com.

## **CONTACT INFORMATION**

Please see the side bar on the right and the front page for the Division nearest to your location.

#### WILLAMETTE VALLEY COMPANY

www.wilvaco.com info@wilvaco.com

## OTHER DIVISIONS

#### PERFORMANCE COATINGS

1075 Arrowsmith Street PO Box 2280 Eugene, OR 97402 Tel 541.484.9621 www.POLYQUIK.com www.wvcorailroad.com

## PRECISION TECHNOLOGIES DIVISION

675 McKinley Street Eugene, OR 97402 Tel 541.484.2368 www.pre-tec.com

#### **SUBSIDIARIES**

#### **CANADIAN WILLAMETTE**

19081- 27<sup>th</sup> Avenue Surrey BC V3S 5T1 Tel. 800.663.4298

#### ECLECTIC PRODUCTS INC.

Corporate Office 1075 Arrowsmith Street Eugene, OR 97402 Tel 541.284.4667 www.eclecticproducts.com

#### **IDAHO MILL & GRAIN**

445 North 430 West Hwy Po Box188 Malad City, Idaho 83252 Tel 208.766.2206

#### TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625 Parque Industrial Coronel Coronel, Chile Tel 011.56.412.928.100 www.tapel.cl



