# **Technical**

# **Data Sheet**



Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service, innovation, and integrity

#### **CENTRALIA DIVISION**

1830 Central Blvd.

Centralia WA 98531

Tel 866.924.9826

# CANADIAN DIVISION SURREY BRANCH

19081-27 Avenue

Surrey BC V3Z 5T1

Tel. 800.663.4298

# MEDFORD BRANCH

736 Mason Way

Medford OR 97501-1354

Tel: 800.888.9826

### TAPEL WILLAMETTE LTD. S.A.

Av Estero la Posada 3625

Parque Industrial Coronel

Coronel Chile

Tel. 011.56.41.2928.100

www.tapel.cl

#### **BATES WILLAMETTE, LLC**

P.O. Box 1328

2242 MacArthur Dr.

Orange TX 77630

Tel. 409.883.0384

# Wil-Fil Filler (Walnut Shell Filler -100)

# **English Walnut Shell**

#### DESCRIPTION

Wil-Fil Filler (Walnut Shell Filler -100) is a pure English Walnut Shell product designed for use in softwood and hardwood plywood adhesives to increase viscosity, reduce cost and improve application. Prior to grinding, the shells are thoroughly cleaned to produce a product that is low in fat content.

#### WHERE TO USE

- Plywood Glue Mixes
- Industrial Mill Environments

#### **FEATURES AND BENEFITS**

- Increases Viscosity easier to process, prevents over penetration and dry-out.
- . Extends the glue mix

### **PACKAGING**

Bulk Sack Quantities Available Fifty-Pound Bags –palletized and shrink wrapped

#### **SHELF LIFE**

12 months when properly stored.

#### STORAGE

Store this product in a clean, dry, shaded or covered environment.

# TECHNICAL INFORMATION

# TYPICAL PROPERTIES

| Screen Analysis<br>(Reynold's Air Swept Particle Size Analyzer)<br>percent through: | 60 mesh  | ≥ 99.5%     |
|---|----------|-------------|
|   | 100 mesh | ≥ 95%       |
|   | 200 mesh | ≥ 70%       |
| Moisture Content (CM5000) +/-2%   |          | 4-10%       |
| Maximum Ash Content (CM5000)  |          | ≤1.5%       |
| Color   |          | Light Brown |

### **NOTES**

This product is supplied to the customer in a ready to use form. Any additions and/or alterations may result in degradation of the product performance.

### **CONTACT INFORMATION**

Please see the side bar for the Sales Office nearest to your location.

#### **HEALTH AND SAFETY**

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS please call 800-333-9826 or send an email to: msds@wilvaco.com.

#### WILLAMETTE VALLEY COMPANY

www.wilvaco.com info@wilvaco.com

#### OTHER DIVISIONS

#### **WESTERN DIVISION**

660 McKinley Street Eugene OR 97402 Tel. 800.333.9826

### MIDWEST DIVISION

1549 Hwy 2 Two Harbors MN 55616 Tel. 218 834 3922

#### **EASTERN DIVISION**

6662 Marbut Road Lithonia GA 30058 Tel. 888.878.9826

#### SOUTHERN DIVISION

100 Dixie Mae Drive Pineville LA 71361 Tel. 800 444 9826

#### PERFORMANCE COATINGS

1075 Arrowsmith Street PO Box 2280 Eugene, OR 97402 Tel 541.484.9621 www.POLYQuik.com www.wvcorailroad.com

# PRECISION TECHNOLOGIES DIVISION

675 McKinley Street Eugene, OR 97402 Tel 541.484.2368 www.pre-tec.com

## **SUBSIDIARIES**

# ECLECTIC PRODUCTS INC.

Corporate Office 1075 Arrowsmith Street Eugene, OR 97402 Tel 541.284.4667 www.eclecticproducts.com

# **IDAHO MILLING & GRAIN**

430 W 445 N PO Box 188 Malad ID 83252 Tel. 208.766.2206



W07-R&D-TDS-035 Revision Date: April 2016

For revisions or latest version please contact: 800 333 9826 ext 5525 or 07julien@wilvaco.com

DISCLAIMER OF WARRANTY