



The Willamette Valley

Company LLC

www.wilvaco.com

www.polyquik.com

800.333.9826

Partnering through service,
innovation, and integrity

FastPatch MD - Slope Grade

Flexible Concrete Repair for Slope Grade Applications

DESCRIPTION

FastPatch MD - Slope Grade is a flexible, two-component urethane designed as a fast curing repair product for concrete repair on sloped areas. FastPatch MD - Slope Grade is designed to be meter dispensed in conjunction with tooling/troweling, and will hold on repairs up to 100% grade (45°).

WHERE TO USE

- Roads/Highways/Bridges
- Trip and Fall Hazards
- Crosswalks and Sidewalks
- Curbs
- Ramps/Transitions
- Any Crack or Spall in Concrete Needing Repair on a Slope

FEATURES AND BENEFITS

- Rapid Cure - as little as 1 hour return to service
- 100% Solids - no odor
- Excellent Concrete Adhesion
- Create Smooth Transitions
- Eliminate Tripping Hazards
- Repair Spalled and Cracked Areas on Ramps and Sloped Substrates

PACKAGING

5-Gallon (19 Liter) Pail
50-Gallon (190 Liter) Drum
200-Gallon (757 Liter) Tote

COLORS

Gray

SHELF LIFE

1 year when properly stored.

STORAGE

Store and ship this product in clean, dry, low-humidity, and shaded or covered environments between 50 and 90°F (10-32°C)

TYPICAL PROPERTIES

	Result	ASTM Method
Solids Content	100%, SCAQMD compliant	D2369
Tack-Free Time	10 minutes	C679
Concrete Adhesion, primed with POLYQuik PolyPrime	500 psi (3.4 MPa) 100% concrete failure	D7234
Working Time, 70°C	4 minutes	-
Hardness	85 Shore A	C661
Mix Ratio (by volume)	1:1	-

APPLICATION INSTRUCTIONS

For applications with WVCO/Pre-Tec metering equipment, training will be provided. If you have specific questions related to your dispensing equipment, please contact your WVCO representative or customer support.

For concrete spall and crack repair guidelines, please refer to: [POLYQuik® Concrete Spall and Crack Repair Guidelines](#).

Contact your WVCO representative for details on how to best repair concrete on a slope.

THE WILLAMETTE VALLEY
COMPANY LLC
www.wilvaco.com
info@wilvaco.com

DIVISIONS

WESTERN DIVISION

990 Owen Loop North
PO Box 2280
Eugene, OR 97402
Tel 541.484.9621
www.POLYQUIK.com
www.SPIKEFAST.com

EASTERN DIVISION

6662 Marbut Road
Lithonia, GA 30058
Tel 888.878.9826

MIDWEST DIVISION

1549 Hwy 2
Two Harbors, MN 55616
Tel 218.834.3922

PRECISION TECHNOLOGIES DIVISION

990 Owen Loop North
Eugene, OR 97402
Tel 541.484.2368
www.pre-tec.com

SOUTHERN DIVISION

100 Dixie Mae Drive
PO Box 4450
Pineville, Louisiana 71361
Tel 318.640.5077

SUBSIDIARIES

ECLECTIC PRODUCTS INC.

Corporate Office
990 Owen Loop North
Eugene, OR 97402
Tel 541.284.4667
www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy
PO Box 188
Malad City, Idaho 83252
Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625
Parque Industrial Coronel
Coronel, Chile
Tel 011.56.41.2.928.100
www.tapel.cl

HEALTH AND SAFETY

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS, please call 800-333-9826 or send an email to: sds@wilvaco.com



W07-R&D-TDS-020
REV 01
Revision Date: August 2020

DISCLAIMER OF WARRANTY
TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE. PROPER APPLICATION IS THE RESPONSIBILITY OF THE USER. AS WITH ANY PRODUCT THE USE OF THIS PRODUCT IN A GIVEN APPLICATION MUST BE TESTED (INCLUDING BUT NOT LIMITED TO FIELD TESTING) IN ADVANCE BY THE USER TO DETERMINE SUITABILITY. TESTING IS THE REQUIREMENT OF BOTH ENGINEERS AND CONTRACTORS ALIKE. WVCO DOES NOT WARRANT THE APPLICATION UNDER ANY OR ALL CIRCUMSTANCES.