

Technical Data Sheet



W V C O

Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service,
innovation, and integrity

CENTRALIA DIVISION

1830 Central Blvd.

Centralia WA 98531

Tel 866.924.9826

CANADIAN WILLAMETTE

19081- 27th Avenue

Surrey BC V3S 5T1

Tel. 800.663.4298

MEDFORD BRANCH

736 Mason Way

Medford OR 97501-1354

Tel: 800.888.9826

TAPEL WILLAMETTE LTD. S.A.

Av Estero la Posada 3625

Parque Industrial Coronel

Coronel Chile

Tel. 011.56.41.2928.100

www.tapel.cl

BATES WILLAMETTE, LLC

P.O. Box 1328

2242 MacArthur Dr.

Orange TX 77630

Tel. 409.883.0384

IMG Premium Extender 200

Wheat Flour Blend Extender for Glue Mixes

DESCRIPTION

IMG Premium Extender 200 is a hard wheat flour based product and a proprietary blend of ingredients. This blend is designed to increase viscosity in plywood adhesive mixes. The substantial protein also increases the prepress tack.

WHERE TO USE

- Plywood Glue Mixes
- Industrial Mill Environments

FEATURES AND BENEFITS

- Increases Viscosity – easier to process, prevents over penetration and dryout.
- Improves Prepress Tack
- High Protein Content

PACKAGING

Large volume bulk bags as well as small bag quantities are available. Please contact your Willamette Valley Representative.

SHELF LIFE

12 months when properly stored.

STORAGE

Store this product in a clean, dry, shaded or covered environment.

TECHNICAL INFORMATION

TYPICAL PROPERTIES

Screen Analysis - percent through mesh (Reynold's Air Swept Particle Analyzer)	100 mesh	> 95%
Moisture Content , +/- 2% (Computrac Max 5000, DICKEY-john)		11%
Maximum Ash Content (Computrac Max 5000, DICKEY-john)		< 2.5%
Protein Content +/- 1.25% (DICKEY-john)		14.25%
Color		Light Tan

NOTES

This product is supplied to the customer in a ready to use form. Any additions may result in degradation of the product performance.

CONTACT INFORMATION

Please see the side bar for the Division nearest to your location.

HEALTH AND SAFETY

Before handling, you should become familiar with the Material Safety Data Sheet (MSDS) regarding the risks and safe use of this product. To obtain an MSDS please call 800-333-9826 or send an email to: msds@wilvaco.com.

WILLAMETTE VALLEY COMPANY

www.wilvaco.com

info@wilvaco.com

OTHER DIVISIONS

WESTERN DIVISION

660 McKinley Street

Eugene OR 97402

Tel. 800.333.9826

MIDWEST DIVISION

1549 Hwy 2

Two Harbors MN 55616

Tel. 218 834 3922

EASTERN DIVISION

6662 Marbut Road

Lithonia GA 30058

Tel. 888.878.9826

SOUTHERN DIVISION

100 Dixie Mae Drive

Pineville LA 71361

Tel. 800 444 9826

PERFORMANCE COATINGS

1075 Arrowsmith Street

PO Box 2280

Eugene, OR 97402

Tel 541.484.9621

www.POLYQuik.com

www.wvcorailroad.com

PRECISION TECHNOLOGIES DIVISION

675 McKinley Street

Eugene, OR 97402

Tel 541.484.2368

www.pre-tec.com

SUBSIDIARIES

ECLECTIC PRODUCTS INC.

Corporate Office

1075 Arrowsmith Street

Eugene, OR 97402

Tel 541.284.4667

www.eclecticproducts.com

IDAHO MILLING & GRAIN

430 W 445 N

P.O. Box 188

Malad ID 83252

Tel. 208.766.2206



Revision Date; February 2013

For revisions or latest version please contact:

Office Coordinator, R&D Eugene

800 333 9826 ext 5525

DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.