Technical

Data Sheet



The Willamette Valley Company LLC

www.wilvaco.com

800.333.9826

Partnering through service, innovation, and integrity

WESTERN DIVISION

660 McKinley Street Eugene OR 97402 Tel. 800.333.9826

EASTERN DIVISION

6662 Marbut Road Lithonia GA 30058 Tel. 888.878.9826

MIDWEST DIVISION

1549 Hwy 2 Two Harbors MN 55616 Tel. 218 834 3922

SOUTHERN DIVISION

100 Dixie Mae Drive Pineville LA 71361 Tel. 800 444 9826

ELVL-2006 Sealers

Water-based Sealer for Wood

DESCRIPTION

ELVL-2006 Sealers are a family of sealers that are water-based products formulated specifically for wood surfaces such as dimensional lumber, laminated veneer lumber and laminated strand lumber. ELVL-2006 Sealer is a surface treatment that minimizes checking, splitting and moisture damage. The ELVL-2006 sealers have excellent water repellency, long lasting outdoor durability, and less stickiness than regular paraffin wax-based sealers. They are economical and environmentally safe products.

WHERE TO USE

- Dimensional Lumber
- Laminated Veneer Lumber
- Laminated Strand Lumber

FEATURES AND BENEFITS

- Sprays Well Through Airless & Air-assisted Pumps
- Smooth Application
- Environmentally Sound
- Excellent Water Repellency
- . Long Lasting Outdoor Durability

PACKAGING

5-gallon pails (18.9-liters) Drums Totes Tank Truck

SHELF LIFE

6 months when properly stored.

STORAGE

Store this product in a clean, dry, shaded or covered environment. DO NOT FREEZE.

TECHNICAL INFORMATION

TYPICAL PROPERTIES

Solids – percent by weight	43%
Viscosity, cps, ASTM D 4878	60
Weight / Gallon – lbs./gallon, (kg/L),	8.2 (0.98)
pH	9.6
Color	Clear and many colors

APPLICATION

ELVL-2006 is designed to work in many delivery systems, including: airless and air-assisted spray systems or brush coating systems. Your Willamette Valley Company representative can advise you as to which product is best for your system.

After application of this material, dry the lumber thoroughly using ambient air or an in-line dryer before stacking. Dry time depends on temperature, humidity and thickness of film.

CLEAN-UP

Clean equipment and containers immediately with hot soapy water.

HEALTH AND SAFETY

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS please call 800-333-9826 or send an email to: msds@wilvaco.com.

NOTES

This product is supplied to the customer in a ready-to-use form. Any addition of water to reduce viscosity may result in degradation of the product performance.

CONTACT INFORMATION

Please see the side bar for the division nearest to your location.

THE WILLAMETTE VALLEY COMPANY LLC

www.wilvaco.com info@wilvaco.com

OTHER DIVISIONS

PERFORMANCE COATINGS

990 Owen Loop North PO Box 2280 Eugene, OR 97402 Tel 541.484.9621 www.POLYQuik.com www.wvcorailroad.com

PRECISION TECHNOLOGIES DIVISION

990 Owen Loop North Eugene, OR 97402 Tel 541.484.2368 www.pre-tec.com

WILLAMETTE VALLEY CO. SURREY DIVISION

19081- 27th Avenue Surrey BC V3S 5T1 Tel. 800.663.4298

SUBSIDIARIES

ECLECTIC PRODUCTS INC.

Corporate Office 990 Owen Loop North Eugene, OR 97402 Tel 541.284.4667 www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy PO Box188 Malad City, Idaho 83252 Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625 Parque Industrial Coronel Coronel, Chile Tel 011.56.41.2928.100 www.tapel.cl



Revision Date: September 2018