

Technical Data Sheet



The Willamette Valley
Company LLC

www.wilvaco.com

800.333.9826

Partnering through
service, innovation, and
integrity

WILLAMETTE VALLEY BV

Spurkt 1B
5804 AR Venray
The Netherlands
+31 478 220020

WESTERN DIVISION

660 McKinley Street
Eugene OR 97402
Tel. 800.333.9826

EASTERN DIVISION

6662 Marbut Road
Lithonia GA 30058
Tel. 888.878.9826

MIDWEST DIVISION

1549 Hwy 2
Two Harbors MN 55616
Tel. 218 834 3922

SOUTHERN DIVISION

100 Dixie Mae Drive
Pineville LA 71361
Tel. 800 444 9826

WIL-PUTTY W.B. FACE FIR

Water-based Filler for Flat Panels

DESCRIPTION

Willamette Valley Company's WIL-PUTTY W.B. FACE FIR is an acrylic-based wood filler used to repair defects in all types of wood. This putty is formulated to be smoothly applied with a flexible putty knife or automated patching systems. Once dried it can be easily sanded, stained, painted and/or overlaid with hardwood surface.

WHERE TO USE

- Flat Panels
- Flooring
- Plywood

FEATURES AND BENEFITS

- Knife Applicable
- Pumpable
- Smooth Application
- Decreased Dry Time
- Reduced Blocking

- Easy Sanding with Excellent Adhesion

PACKAGING

5-Gallon pails
Drums
Totes

SHELF LIFE

12 months when properly stored.

STORAGE

Store this product in a clean, dry, shaded or covered environment. DO NOT FREEZE.

TECHNICAL INFORMATION

TYPICAL PROPERTIES

Percent Solids by Weight	73±2%
Viscosity, cps, Spindle C, 2.5 rpm, @77 °F	80,000 cP
Density	14.2 lb/gal 1.7 kg/l
Color	Woodtones

DRY TIME

A thin film will dry in minutes. Thicker applications may require hours to dry. Dry time depends on temperature, humidity and thickness of film.

CLEAN-UP

WIL-PUTTY W.B. FACE FIR can be washed with water prior to drying. If it has dried, steam or mechanical abrasion is recommended.

NOTES

This product is supplied to the customer in a ready to use form. Any addition of water to reduce viscosity may result in degradation of the product performance.

CONTACT INFORMATION

Please see the side bar for the Division nearest to your location.

APPLICATION

This product is formulated to be applied in woodworking shops and industrial mill applications with a flexible blade putty knife. For other methods of application, check with your Willamette Valley Company Representative.

HEALTH AND SAFETY

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS please call 800 333 9826 or send an email to: msds@wilvaco.com.

THE WILLAMETTE VALLEY COMPANY LLC

www.wilvaco.com
info@wilvaco.com

OTHER DIVISIONS

PERFORMANCE COATINGS

990 Owen Loop North
PO Box 2280
Eugene, OR 97402
Tel 541.484.9621
www.POLYQuik.com
www.wvcorailroad.com

PRECISION TECHNOLOGIES DIVISION

990 Owen Loop North
Eugene, OR 97402
Tel 541.484.2368
www.pre-tec.com

CANADIAN DIVISION SURREY BRANCH

19081- 27th Avenue
Surrey BC V3S 5T1
Tel. 800.663.4298

SUBSIDIARIES

ECLECTIC PRODUCTS INC.

Corporate Office
990 Owen Loop North
Eugene, OR 97402
Tel 541.284.4667
www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy
PO Box 188
Malad City, Idaho 83252
Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625
Parque Industrial Coronel
Coronel, Chile
Tel 011.56.41.2928.100
www.tapel.cl



DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.

W07-R&D-TDS-162

Rev 00

Revision Date: December 2019