

Technical Data Sheet



Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service,
innovation, and integrity

WESTERN DIVISION

660 McKinley Street

Eugene OR 97402

Tel. 800.333.9826

EASTERN DIVISION

6662 Marbut Road

Lithonia GA 30058

Tel. 888.878.9826

MIDWEST DIVISION

1549 Hwy 2

Two Harbors MN 55616

Tel. 218 834 3922

SOUTHERN DIVISION

100 Dixie Mae Drive

Pineville LA 71361

Tel. 800 444 9826

Perma Seal LS Orange

Edge Sealer for Engineered and Dimensional Lumber

DESCRIPTION

Perma Seal LS Orange is formulated as a high quality edge sealer specifically designed to meet the needs of the engineered wood products industry. The sealer minimizes checking, splitting and moisture damage which cause the dimensional instability of wood substrates. Perma Seal LS Orange has excellent water repellency and is an economical and environmentally safe product.

WHERE TO USE

- Engineered and Dimensional Lumber & Panel:
 - LSL, LVL, OSB, Plywood, Particle Board
- Industrial Mill Environments

FEATURES AND BENEFITS

- Excellent Water Repellency and Moisture Protection
- Easy Application
- Environmentally Sound
- Long Lasting Moisture Barrier

PACKAGING

Pails
Drums
Totes
Tankers

SHELF LIFE

3 months when properly stored.

STORAGE

Store this product in a clean, dry, shaded or covered environment above 45°F. DO NOT FREEZE.

TECHNICAL INFORMATION

TYPICAL PROPERTIES

pH (varies dependent on color)	9.5
Solids by weight	23.5%
Viscosity at 78°F (centipoise)	650 cps
Color – Orange and Many Standard and Custom Colors Available	

APPLICATION

Perma Seal LS Orange is designed to work in many delivery systems, including: airless and air-assisted spray systems or brush coater systems. Apply one coat of sealer at a wet film thickness of less or equal to 7 wet mils. The film thickness can be adjusted for porous wood or to obtain a higher protection performance. Check with your Willamette Valley Company representative for directions and recommendations.

CLEAN-UP

Clean Perma Seal LS Orange from equipment and containers immediately with hot soapy water.

NOTES

This product is supplied to the customer in a ready to use form. Any addition of water will result in degradation of the product performance.

HEALTH AND SAFETY

Willamette Valley Company recommends reading and becoming familiar with the Material Safety Data Sheet before using this product.

CONTACT INFORMATION

Please see the side bar on the right and the front page for the Division nearest to your location.

WILLAMETTE VALLEY COMPANY

www.wilvaco.com
info@wilvaco.com

OTHER DIVISIONS

PERFORMANCE COATINGS

1075 Arrowsmith Street
PO Box 2280
Eugene, OR 97402
Tel 541.484.9621
www.POLYQUIK.com
www.wvcorailroad.com

PRECISION TECHNOLOGIES DIVISION

675 McKinley Street
Eugene, OR 97402
Tel 541.484.2368
www.pre-tec.com

SUBSIDIARIES

CANADIAN WILLAMETTE

325 Edworthy Way
New Westminster BC V3L 5G4
Tel. 800.663.4298

ECLECTIC PRODUCTS INC.

Corporate Office
1075 Arrowsmith Street
Eugene, OR 97402
Tel 541.284.4667
www.eclecticproducts.com

IDAHO MILL & GRAIN

445 North 430 West Hwy
Po Box 188
Malad City, Idaho 83252
Tel 208.766.2206

TAPEL WILLAMETTE LTD. S.A.

Av. Estero La Posada 3625 Parque
Industrial Coronel Coronel, Chile
Tel 011.56.41.928.100
www.tapel.cl

DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE.



Revision Date: October 2009