## **Technical**

# **Data Sheet**



Willamette Valley Company

www.wilvaco.com

800.333.9826

Partnering through service, innovation, and integrity

### **CENTRALIA DIVISION**

1830 Central Blvd.

Centralia WA 98531

Tel 866.924.9826

### **CANADIAN WILLAMETTE**

19081-27th Avenue

Surrey BC V3S 5T1

Tel. 800.663.4298

### **MEDFORD BRANCH**

736 Mason Way

Medford OR 97501-1354

Tel: 800.888.9826

### **TAPEL WILLAMETTE LTD. S.A.**

Av Estero la Posada 3625

**Parque Industrial Coronel** 

Coronel Chile

Tel. 011.56.41.2928.100

www.tapel.cl

### **BATES WILLAMETTE, LLC**

P.O. Box 1328

2242 MacArthur Dr.

Orange TX 77630

Tel. 409.883.0384

# **SUPER BOND**

### Alder Bark Flour

#### DESCRIPTION

Super Bond is a filler for phenolic resin adhesives used in the plywood industry. It is a cost effective bulking agent with over forty years of proven performance.

### WHERE TO USE

- Plywood Glue Mixes
- Industrial Mill Environments

### FEATURES AND BENEFITS

- Blends Smoothly into Glue Formula
- Low Moisture and Ash Content
- Consistent Uniformity for Reproducible Glue Mix Results
- Controls Glue Spread and Penetration
- Promotes Stable Viscosity and Excellent Pre-Press

### **PACKAGING**

Bulk- 2000 lb., 1800lb., 1390 lb.

Bags – 50 lbs in paper sacks, palletized and shrink wrapped

### **SHELF LIFE**

12 months when properly stored.

### **STORAGE**

Store this product in a clean, dry, shaded or covered environment.

### **TECHNICAL INFORMATION**

### TYPICAL PROPERTIES

Fineness - percent through mesh (Reynold's Air Swept Particle Size Analyzer)	60	99%
	100	98%
	200	76%
Moisture Content (Computrac Max 5000) +/-2%		5%
Maximum Ash Content (Computrac Max 5000)		< 8%
Color		Dark Brown

### NOTES

This product is supplied to the customer in a ready to use form. Any additions may result in degradation of the product performance.

### CONTACT INFORMATION

Please see the side bar for the Division nearest to your location.

### **HEALTH AND SAFETY**

Before handling, you should become familiar with the Material Safety Data Sheet (MSDS) regarding the risks and safe use of this product. To obtain an MSDS please call 800-333-9826 or send an email to: msds@wilvaco.com.

### **WILLAMETTE VALLEY COMPANY**

www.wilvaco.com info@wilvaco.com

### OTHER DIVISIONS

#### WESTERN DIVISION

660 McKinley Street Eugene OR 97402 Tel. 800.333.9826

### MIDWEST DIVISION

1549 Hwy 2 Two Harbors MN 55616 Tel. 218 834 3922

### **EASTERN DIVISION**

6662 Marbut Road Lithonia GA 30058 Tel. 888.878.9826

### SOUTHERN DIVISION

100 Dixie Mae Drive Pineville LA 71361 Tel. 800 444 9826

### PERFORMANCE COATINGS

1075 Arrowsmith Street PO Box 2280 Eugene, OR 97402 Tel 541.484.9621 www.POLYQuik.com www.wycorailroad.com

### PRECISION TECHNOLOGIES DIVISION

675 McKinley Street Eugene, OR 97402 Tel 541.484.2368 www.pre-tec.com

#### **SUBSIDIARIES**

### ECLECTIC PRODUCTS INC.

Corporate Office 1075 Arrowsmith Street Eugene, OR 97402 Tel 541.284.4667 www.eclecticproducts.com

### **IDAHO MILLING & GRAIN**

430 W 445 N P.O. Box 188 Malad ID 83252 Tel. 208.766.2206



Revision Date; May 2012
For revisions or latest version please contact:
Office Coordinator, R&D Eugene
800 333 9826 ext 5525

#### DISCI AIMER OF WARRANTY